



Relpol relay for printed circuit AC220V AC250V 8A RM84-2012-35-5230



Product codes:

Reference: REP0051002

EAN13: -

UPC: -

Product description:

Relpol relay for printed circuit AC220V AC250V 8A RM84-2012-35-5230

Manufacturer: RELPOL

Type of electromagnetic relay

Contact configuration: DPDT

Rated voltage of inductor: 230V AC

Max current of contacts: 8A

Contact load capacity AC @R (at resistive load): 8A / 250V AC

Contact load capacity DC @R (at resistive load): 8A / 24V DC

Max connected voltage: 250V DC, max. 440V AC

Miniature relay version

PCB mounting

Inductor resistance: 38500?

Min inductor voltage: 184V AC

Max inductor voltage: 276V AC

Operating time: 7ms

Internal dimensions: 29x12.7x15.7mm

Turn-off time: 3ms



Shop name

Power consumption of inductor: 750mVA
Ingress protection class: IP67
Mechanical durability: 30,000,000 cycles
Operating temperature: -40...85°C
Relay series: RM84
Contact resistance: 100mΩ
Contact material: AgNi
Terminal pitch: 5mm
Height: 15.7mm
Number of pins: 8
Case color: white

Product features:

Application: Washing
Dishwasher Parts: Electronic Parts
Compatible Brands: Oztiryakiler
Compatible Brands: Finder
Compatible Brands: Relpol
Electrical Components: Relays
Types of Relays: Printed circuit relay

Product short description:

Product gallery: