

Industrial scale TMN 30 P 260659



Product codes:

Reference: 260659

EAN13: -UPC: -

Product description:

FEATURES:

- Tubular structure platform in painted steel, with stainless steel plate and stainless steel column.
- Aluminum cell with IP65 protection.
- Column with painted steel base (model P447 mm).
- 4 adjustable feet in height up to an increase of 13 mm.
- Length of platform-display cable: 1200 mm (up to 1370 mm, depending on model).
- CE certification.
- Approval to 3000 divisions OIML class III.
- Indicator in ABS, model BR16.
- IP54 protection.
- Waterproof keyboard with 6 function keys and power on/off keys.
- Large backlit LCD display with 6 digits of 40 mm.
- Display backlighting with three modes: automatic, activated, and deactivated.
- ABS support for column.
- Includes wall anchoring holes.
- Operating temperature: -10°C +40°C.
- Power supply with AC/DC adapter 240Vac 50Hz.



- Rechargeable battery 6V/4Ah.
- Battery life with backlighting activated: approx. 80 hours.
- Battery life with backlighting deactivated: approx. 320 hours.
- Units kg or t or g (to be chosen at the time of order).
- Single range/Multi range (to be chosen at the time of order).
- Automatic disconnection (with desired time setting from 1 to 99 minutes).

FUNCTIONS:

- Accumulation (Only outside of legal metrology)
- Totalization
- Piece counting
- Zero
- Four hold modes: off, moving animal, peak value, stable, and stable with auto cancellation to zero
- Weight and piece control (limit function) with visual signal and alarm
- Three speeds of the AD converter (high, medium, and low)
- Configurable gravity (without legal metrology)
- Gross/Net
- Tare

Product features:

Plate dimensions (mm): 350x450

Capacity (kg): 30 Kg Weight fraction (g): 10 g

Verification: Yes

Weighing: Floor Scale

Product short description:

















Product gallery:



