



# Industrial scale TMN 150 G 260665



## Product codes:

Reference: 260665

EAN13: -

UPC: -



## Product description:

### FEATURES:

- Platform with tubular structure in painted steel, with plate in stainless steel and column in stainless steel.
- Aluminum cell with IP65 protection.
- Column with painted steel base for mounting (model P447 mm).
- 4 adjustable feet in height up to an increase of 13 mm.
- Length of cable platform-display: 1200 mm (up to 1370 mm, depending on the model).
- CE certification.
- Approval for 3000 divisions OIML class III.
- Indicator in ABS, model BR16.
- IP54 protection.
- Waterproof keyboard with 6 function keys and power on/off keys.
- Large backlit LCD display with 6 digits of 40 mm.



- 
- Display backlighting with three modes: automatic, activated, and deactivated.
  - ABS support for the column.
  - Includes wall anchoring holes.
  - Operating temperature:  $-10^{\circ}\text{C}$   $+40^{\circ}\text{C}$ .
  - Power supply from mains with AC/DC adapter 240Vac 50Hz.
  - Rechargeable battery 6V/4Ah.
  - Battery life with backlighting activated: approx. 80 hours.
  - Battery life with backlighting deactivated: approx. 320 hours.
  - Units kg or t or g (to be chosen at the time of order).
  - Single range/Multi range (to be chosen at the time of order).
  - Automatic disconnection (with desired time configuration from 1 to 99 minutes).

**FUNCTIONS:**

- Accumulation (Only outside legal metrology)
- Totalization
- Piece counting
- Zero
- Four hold modes: off, moving animal, peak value, stable and stable with auto zero cancellation
- Weight and piece control (limit function) with visual signal and alarm
- Three speeds of the AD converter (high, medium, and low)
- Configurable gravity (without legal metrology)
- Gross/Net
- Tare

**Product features:**

Plate dimensions (mm): 500x600

Capacity (kg): 150 kg

Weight fraction (g): 50 g

Verification: Yes

Weighing: Floor Scale

**Product short description:**

---



Shop name



PCS



CHECK



MOVE



BAT INT



AC/DC



IP54



VERIF

Product gallery:

