



Industrial scale TMN 300 G 260666



Product codes:

Reference: 260666

EAN13: -

UPC: -

Product description:

FEATURES:

- Platform with a tubular structure in painted steel, with a tray in stainless steel and a column in stainless steel.
 - Cell in aluminum with IP65 protection.
 - Column with a fixed base in painted steel (model P447 mm).
 - 4 adjustable feet in height up to an increase of 13 mm.
 - Length of cable platform-display: 1200 mm (up to 1370 mm, depending on the model).
 - CE certification.
 - Approval for 3000 divisions OIML class III.
 - Indicator in ABS, model BR16.
 - IP54 protection.
 - Waterproof keyboard with 6 function keys and power on/off keys.
 - Large backlit LCD display with 6 digits of 40 mm.
 - Display backlighting with three modes: automatic, activated, and deactivated.
 - ABS support for the column.
 - Includes wall mounting holes.
 - Operating temperature: -10°C $+40^{\circ}\text{C}$.
 - Power supply with AC/DC adapter 240Vac 50Hz.
-



- Rechargeable battery 6V/4Ah.
- Battery life with backlighting activated: approximately 80 hours.
- Battery life with backlighting deactivated: approximately 320 hours.
- Units kg or t or g (to be chosen at the time of order).
- Unit range/Multi range (to be chosen at the time of order).
- Automatic disconnection (with desired time configuration from 1 to 99 minutes).

FUNCTIONS:

- Accumulation (Only outside of legal metrology)
- Totalization
- Piece counting
- Zero
- Four hold modes: off, moving animal, peak value, stable, and stable with auto cancel to zero
- Weight and piece control (limit function) with visual signal and alarm
- Three speeds of the AD converter (high, medium, and low)
- Configurable gravity (without legal metrology)
- Gross/Net
- Tare

Product features:

Plate dimensions (mm): 500x600

Capacity (kg): 300 kg

Weight fraction (g): 100 g

Verification: Yes

Weighing: Floor Scale

Product short description:



PCS



CHECK



MOVE



BAT INT



AC/DC



IP54



VERIF



Shop name

Product gallery:

