



Industrial scale TMZ 30 P 260585



Product codes:

Reference: 260585

EAN13: -

UPC: -

Product description:

FEATURES:

- Platform with tubular structure in painted steel, with a stainless steel plate and stainless steel column.
 - Aluminum cell with IP65 protection.
 - Column of 649mm with painted steel fixing base (model P447 mm).
 - 4 adjustable feet in height up to an increase of 13 mm.
 - Cable length platform-display: 1200 mm (up to 1370 mm, depending on the model).
 - Indicator in ABS, model BR15.
 - IP54 protection.
 - Waterproof keyboard with 5 function keys and on/off keys.
 - Backlit LCD display with 6 digits of 30 mm.
 - Display backlighting with three modes: automatic, activated, and deactivated.
 - ABS support for column.
 - Includes wall anchoring holes.
 - Operating temperature: -10°C to $+40^{\circ}\text{C}$.
 - Powered by AC with AC/DC adapter 240Vac 50Hz.
 - Rechargeable battery 6V/4Ah.
 - Battery duration with backlighting activated: approx. 120 hours.
-



Shop name

- Battery duration with backlighting deactivated: approx. 160 hours.
- Configurable gravity.
- Unit 1 to choose from off, kg, t, and g; Unit 2 to choose from off, lb, lboz; Unit 3 to choose from off, Taiwan Jin, CA, or VISS.
- RS232 output. Data transmission in PC and printer format.
- Unit range / Multi range / Multi interval.
- Automatic disconnection (with desired time setting from 1 to 99 minutes).

FUNCTIONS:

- Accumulation
- Totalization
- Piece counting
- Zero
- Four hold modes: disabled, moving animal, peak value, stable, and stable with automatic zero cancellation
- Weight and piece control (limit function) with visual signal and alarm
- Three speeds of the AD converter (high, medium, and low)
- Configurable gravity
- Gross/Net
- Tare

Product features:

Plate dimensions (mm): 450x350

Capacity (kg): 30 Kg

Weight fraction (g): 5gr

Verification: No

Weighing: Floor Scale

Product short description:



PCS



CHECK



MOVE



RS232



RS232



BAT INT



AC/DC



IP54



NO VERIF



Shop name

Product gallery:

