



Industrial Scale TMZ 60 M 260589



Product codes:

Reference: 260589

EAN13: -

UPC: -

Product description:

FEATURES:

- Tubular structure platform made of painted steel, with a plate in stainless steel and a column in stainless steel.
 - Aluminum cell with IP65 protection.
 - Column of 649mm with painted steel fixing base (model P447 mm).
 - 4 adjustable feet in height up to an increase of 13 mm.
 - Length of platform-display cable: 1200 mm (up to 1370 mm, depending on model).
 - Indicator in ABS, model BR15.
 - IP54 protection.
 - Waterproof keyboard with 5 function keys and power on/off keys.
 - Backlit LCD display with 6 digits of 30 mm.
 - Display backlighting with three modes: automatic, activated, and deactivated.
 - ABS support for column.
 - Includes wall anchoring holes.
 - Operating temperature: -10°C $+40^{\circ}\text{C}$.
 - Power supply with AC/DC adapter 240Vac 50Hz.
 - Rechargeable battery 6V/4Ah.
 - Battery life with backlighting activated: approximately 120 hours.
-



Shop name

- Battery life with backlighting deactivated: approximately 160 hours.
- Configurable gravity
- Unit 1 to choose from off, kg, t, and g; Unit 2 to choose from off, lb, lboz; Unit 3 to choose from off, Taiwan Jin, CA, or VISS.
- RS232 output. Data transmission in PC and printer format.
- Unit range / Multi range / Multi interval.
- Automatic disconnection (with desired time setting from 1 to 99 minutes).

FUNCTIONS:

- Accumulation
- Totalization
- Piece counting
- Zero
- Four hold modes: off, moving animal, peak value, stable, and stable with auto cancellation to zero
- Weight and piece control (limit function) with visual signal and alarm
- Three speeds of the AD converter (high, medium, and low)
- Configurable gravity
- Gross/Net
- Tare

Product features:

Plate dimensions (mm): 500x400

Capacity (kg): 60 kg

Weight fraction (g): 10 g

Verification: No

Weighing: Floor Scale

Product short description:



PCS



CHECK



MOVE



RS232



RS232



BAT INT



AC/DC



IP54



NO VERIF



Shop name

Product gallery:

