



LKZ 12/12-6T 1 1/2M Extraction Box



Product codes:

Reference: 9049C

EAN13: -

UPC: -

Product description:

Material and Design

- Enclosure made of **galvanized steel** with anti-corrosive treatment.
- Turbine with blades curved forward, also made of galvanized sheet.
- **Includes blind cover** to facilitate installation in extraction systems.
- Electrical connection via **splice connector**.
- Robust, compact design, prepared for intensive use.

Technical Specifications

- **Motor:** High efficiency, in accordance with ErP 2015 regulations.
 - **Motor type:** Closed, with built-in thermal protector, class F, with ball bearings.
 - **Protection:** IP54.
 - **Speed:** 900 rpm (1 speed).
-



-
- **Voltage:** Three-phase 380 V AC – 50 Hz.
 - **Power:** 1,100 W.
 - **Air flow:** 7800 m³/h.
 - **Sound level:** 75 dB.
 - **Air temperature to be transported:** -20 °C to +60 °C.

Included Equipment

- Extraction box with turbine and pre-assembled motor.
- Blind cover.
- Electrical connection plug.

Additional Features

- High extraction flow for large spaces or with high thermal load.
- Quiet operation relative to its power.
- Durable and resistant materials for demanding environments.
- Compatible with centralized or local ventilation installations.

Product features:

Power Supply Voltage: 380-400V 50Hz

Power Watts: 1100W

Hospitality Furniture: Bells Accessories

Bells Accessories: Extraction Box

Product short description:



High-performance industrial extraction box, designed to move large volumes of air in installations requiring power, efficiency, and reliability. Ideal for demanding applications in professional kitchens, industrial warehouses, and general ventilation systems.

Product gallery:

