

Extraction box LKZ 9/9-4M 1/2M



Product codes:

Reference: 9041C EAN13: -

UPC: -

Product description:

Material and Design

Structure made of **galvanized steel sheet** with anti-corrosion treatment.

Turbine with forward-curved blades in galvanized steel sheet.

Includes blind cover.

Electrical connection via splice connector.

Robust and compact design with materials resistant to corrosion.



Technical Specifications

Motor: High efficiency (HE), compliant with ErP 2015 regulations.

Motor type: Closed, with built-in thermal protector, class F, with ball bearings.

Protection: IP54.

Speed: 1250 rpm (1 speed).

Voltage: Single-phase 220-240 V AC – 50 Hz.

Power: 370 W.

Air flow: 2800 m³/h.

Sound level: 70 dB.

Temperature of the air to be transported: -20 °C to +60 °C.

Condenser: 20 ?F.



Included Equipment

•				

Extraction box with pre-mounted turbine.

Blind cover.

Electrical connection connector.

Additional Features

Quiet and efficient operation.

Ideal for centralized ventilation systems or localized extraction areas.

Long-lasting components designed for industrial environments.

Product features:

Power Supply Voltage: 220-240V 50Hz

Power Watts: 370W

Hospitality Furniture: Bells Accessories

Bells Accessories: Extraction Box

Product short description:



High-performance extraction box designed for industrial and commercial ventilation systems. It offers excellent airflow capacity with low maintenance, ideal for demanding applications where reliability and energy efficiency are required.

Product gallery:





