



AC3 Contactor 18A, 380VAC Coil, 3 Poles, 3 NO Contacts, 1 Auxiliary NO Contact, CJX2-1810



Product codes:

Reference: REP0096006

EAN13: -

UPC: -

Product description:

AC3 Contactor 18A, 380VAC Coil, 3 Poles, 3 NO Contacts, 1 Auxiliary NO Contact, CJX2-1810

Model: CJX2-1810

Rated Current (AC-3): 18 A

Rated Current (AC-1): 32 A

Maximum Motor Power (AC-3): 7.5 kW (400 V)

Operating Voltage: Up to 690 V AC

Utilization Category: AC-3

Number of Main Poles: 3

Auxiliary Contacts: 1 NO

Operating Frequency: 1200 cycles/h (AC-3)

Coil Voltage: 380 V AC

Electrical Durability: 1 million operations

Mechanical Durability: 10 million operations



Mounting: DIN rail or screws
Operating Temperature: -5 °C to +55 °C
Applicable Standard: IEC 60947-4-1

Applications:
Starting and stopping three-phase motors
Controlling pumps, fans, and compressors
Electrical panels and automation systems

AC-1 Resistive: Heating, ovens

AC-2 Loop motor: Cranes, mills

AC-3 Squirrel cage motor: Pumps, compressors, fans

AC-4 Squirrel cage motor (reversing/braking): Elevators, cranes, presses

Product features:

Nominal Current AC1: 32A
Nominal Current AC3: 18 A
Coil: 400V
Auxiliary Contact: NO
Current Amperes: 32A
Electrical Components: Contactor
Type of contactor: AC3
Main Contacts: 3NO

Product short description:

Product gallery:



Shop name

